

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 1/23

**All American 50 Finish**

---

## **SECTION 1: Identification**

### **Product identifier**

**Product name:** All American 50 Finish

### **Recommended use of the product and restriction on use**

**Relevant identified uses:** Finishes, Coatings, and Related Materials

**Uses advised against:** For Professional Use Only

**Reasons why uses advised against:** Not determined or not applicable.

### **Manufacturer or supplier details**

#### **United States**

Floor Care Concepts and Supply

3714 Buchanan St SW

Wyoming, MI 49548

800-491-0455

#### **Emergency telephone number:**

#### **United States**

Infotrac: 1-800-535-5053 (24/7)

## **SECTION 2: Hazard(s) identification**

### **GHS classification:**

Skin irritation, category 2

Eye irritation, category 2A

Flammable liquids, category 3

Skin sensitization, category 1

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 2/23

**All American 50 Finish**

---

Germ cell mutagenicity, category 1B

Carcinogenicity, category 1B

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3,

narcotic effects Specific target organ toxicity - repeated exposure, category 1

### Label elements

#### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H226 Flammable liquid and vapor

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H340 May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H350 May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard) H336 May cause drowsiness or dizziness

H372 Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

#### Precautionary statements:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 3/23

**All American 50 Finish**

---

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge P261 Avoid breathing dust/fume/gas/mist/vapors/spray P272 Contaminated work clothing must not be allowed out of the workplace P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood P271 Use only outdoors or in a well-ventilated area P260 Do not breathe dust/fume/gas/mist/vapors/spray P270 Do not eat, drink or smoke when using this product P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention P362 Take off contaminated clothing and wash it before re-use P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish P333+P313 If skin irritation or rash occurs: Get medical advice/attention P363 Wash contaminated clothing before reuse

P308+P313 IF exposed or concerned: Get medical advice/attention P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P312 Call a POISON CENTER/doctor/.../if you feel unwell P314 Get medical advice/attention if you feel unwell P403+P235 Store in a well-ventilated place. Keep cool P405 Store locked up

P403+P233 Store in a well-ventilated place. Keep container tightly closed P501 Dispose of contents/container to...

**Hazards not otherwise classified:** None

### **SECTION 3: Composition/information on ingredients**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 4/23

**All American 50 Finish**

Identification	Name	Weight %
CAS number: 8001-26-1	Linseed Oil	3-6
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	35-45
CAS number: 8052-41-3	Stoddard Solvent with < 0.1% Benzene content	2.5-4.5
CAS number: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	<4

**Additional Information:** None

### **SECTION 4: First aid measures**

#### **Description of first aid measures**

**General notes:** Show this Safety Data Sheet to the doctor in attendance.

**After inhalation:** If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

**After skin contact:** Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

**After eye contact:** Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention. Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

**After swallowing:** If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 5/23

**All American 50 Finish**

---

### **Most important symptoms and effects, both acute and delayed Acute symptoms and effects:**

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Generated using Total SDS™ (patent-pending), [www.GSMSDS.com](http://www.GSMSDS.com)

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

### **Delayed symptoms and effects:**

Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause genetic defects.

Exposure may cause cancer.

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Causes damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

### **Immediate medical attention and special treatment Specific treatment:**

Effects are dependent on exposure (dose, concentration, contact time).

Overexposure via inhalation requires urgent medical treatment.

### **Notes for the doctor:**

Treat symptomatically.

### **SECTION 5: Firefighting measures**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 6/23

**All American 50 Finish**

---

### Extinguishing media

#### Suitable extinguishing media:

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable extinguishing media:

Do not use water jet.

#### Specific hazards during fire-fighting:

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Thermal decomposition may produce irritating/toxic fumes/gases.

**Special protective equipment for firefighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

#### Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions.

Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water Generated using Total SDS™ (patent-pending), [www.GSMSDS.com](http://www.GSMSDS.com)

spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 7/23

**All American 50 Finish**

---

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

### **SECTION 6: Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

Wear recommended personal protective equipment (See Section 8).

Avoid contact with eyes, skin and clothing. Eliminate all sources of ignition.

Ensure adequate ventilation.

Shut off all possible sources of ignition and avoid friction and impact.

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Isolate and post spill area.

Remove all sources of ignition.

Ventilate the area.

Wear suitable protective clothing, gloves and eye/face protection.

For personal protection see section 8

Isolate and post spill area. Remove all sources of ignition. Ventilate the area. Wear suitable protective clothing, gloves and eye/face protection. For personal protection see section 8

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 8/23

---

### **All American 50 Finish**

and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist.

vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and laundry before reuse.

#### **Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

If contamination of sewers or waterways has occurred advise local emergency services.

Avoid discharge into drains, water courses or onto the ground. Prevent further leakage if safe to do so.

Inform authorities if spill cannot be contained.

Keep material out of lakes, streams, ponds, and sewer drains.

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways.

Discharge into the environment must be avoided.

**Methods and material for containment and cleaning up:** Carefully sweep material into a designated PLASTIC waste container. Collect in plastic containers only.

Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal.

Vacuum or sweep up material and place into a suitable disposal container. Wear a self-contained breathing apparatus and appropriate personal protection. Provide ventilation.

Clean and neutralize spill area, tools and equipment by washing with water and soap.

Absorb rinsate and add to the collected waste.

Waste must be classified and labeled prior to recycling or disposal.



## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 9/23

**All American 50 Finish**

---

Dispose of waste as indicated in Section 13.

Clean and neutralize spill area, tools and equipment by washing with water and soap. Absorb rinsate and add to the collected waste. Waste must be classified and labeled prior to recycling or disposal. Dispose of waste as indicated in Section 13.

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### **Reference to other sections:**

For disposal see section 13.

For further information refer to section 7 and section 13.

For personal protective equipment see Section 8. For disposal see Section 13.

### **SECTION 7: Handling and storage**

#### **Precautions for safe handling:**

Wear gloves and eye protection when handling, moving or using this product. Do not contaminate water, food, or feed by storage or disposal.

Avoid skin and eye contact and breathing in vapor. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc.) must be eliminated both in and near the work area. Do NOT smoke. Take precautionary measures against static discharges. Wash hands thoroughly after handling.

Avoid contact with skin, eyes, and clothing. Follow good hygiene procedures when handling chemical materials. Refer to Section 8. Follow proper disposal methods. Refer to Section 13. Do not eat, drink, smoke, or use personal products when handling chemical substances.

Avoid contact with skin, eyes, and clothing.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 10/23

**All American 50 Finish**

---

Follow good hygiene procedures when handling chemical materials. Refer to Section 8.

Follow proper disposal methods. Refer to Section 13.

Do not eat, drink, smoke, or use personal products when handling chemical substances.

Follow good hygiene procedures when handling chemical materials.

Refer to Section 8.

Follow proper disposal methods.

Refer to Section 13.

Avoid breathing dust/ fume/ gas/mist/vapors/spray. Keep away from all sources of ignition. Avoid contact with skin and eyes.

**Conditions for safe storage, including any incompatibilities:** Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use Store in a cool, dry, well ventilated place.

Store away from sources of heat or ignition.

Store away from incompatible materials described in Section 10.

Keep containers closed when not in use

Store in cool location. Keep away from food and beverages. Protect from freezing and physical damage.

Provide ventilation for containers. Keep container tightly sealed. Store away from incompatible materials.

Store in cool, dry place and keep container tightly closed. Do not store in direct sunlight.

### **SECTION 8: Exposure controls/personal protection**

Only those substances with limit values have been included below.

#### **Occupational Exposure limit values:**

<b>Country (Legal Basis)</b>	<b>Substance</b>	<b>Identifier</b>	<b>Permissible concentration</b>
United States	Linseed Oil	8001-26-1	TWA: 15 mg/m <sup>3</sup> (Total dust)
	Linseed Oil	8001-26-1	TWA: 5 mg/m <sup>3</sup> (Respirable fraction)

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

**Page 11/23**

### All American 50 Finish

NIOSH up to  week)	Linseed Oil	8001-26-1	REL: 10 mg/m <sup>3</sup> (Vegetable oil\mist, Total; for  a 10-hour, workday during a 40-hour work-
ble; for up  workweek)	Linseed Oil	8001-26-1	REL: 5 mg/m <sup>3</sup> (Vegetable oil mist, Respira-  to a 10-hour, workday during a 40-hour
	Stoddard Solvent with < 0.1% Benzene	8052-41-3	Ceiling Limit: 1800 mg/m <sup>3</sup> (15-content min)
	Stoddard Solvent with < 0.1% Benzene	8052-41-3	IDLH: 20000 mg/m <sup>3</sup> content
	Stoddard Solvent with < 0.1% Benzene	8052-41-3	REL: 350 mg/m <sup>3</sup> content
sure limit REL  workweek)	Solvent naphtha  (petroleum), heavy arom.	64742-94-5	REL: 100 mg/m <sup>3</sup> (NIOSH Recommended expo-  [for up to a 10-hour workday during a 40-hour
OSHA	Stoddard Solvent with < 0.1% Benzene	8052-41-3	PEL: 525 mg/m <sup>3</sup> content
	Stoddard Solvent with < 0.1% Benzene	8052-41-3	PEL: 100 ppm content
<b>Country (Legal Basis)</b>	<b>Substance</b>	<b>Identifier</b>	<b>Permissible concentration</b>
ACGIH	Stoddard Solvent	8052-41-3	8-Hour TWA: 100 ppm content

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 12/23

---

### All American 50 Finish

with < 0.1% Benzene

Solvent naphtha                      64742-94-5                      8-Hour TWA: 200 mg/m<sup>3</sup>  
(petroleum), heavy arom.

United States(California)              Stoddard Solvent                      8052-41-3                      8-Hour TWA: 100 ppm content

with < 0.1% Benzene

Stoddard Solvent                      8052-41-3                      8-Hour TWA: 525 mg/m<sup>3</sup>content

with < 0.1% Benzene

**Biological limit values:** No biological exposure limits noted for the ingredient(s).

**Information on monitoring procedures:** Not determined or not applicable.

#### Appropriate engineering controls:

Effective ventilation in all processing areas.

Use local exhaust ventilation to maintain airborne concentrations below the TLV.

#### Personal protection equipment

**Eye and face protection:** Safety goggles or safety glasses with side shields Safety glasses

**Skin and body protection:** Impervious clothing, chemical resistant gloves

Chemical resistant clothing and gloves

Impervious clothing and chemical resistant gloves Impervious clothing, Chemical resistant gloves

Chemical resistant clothing, chemical resistant gloves

**Respiratory protection:** In case of insufficient ventilation, wear suitable respiratory protection In case of insufficient ventilation, wear suitable respiratory protection

#### General hygienic measures:

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 13/23

---

### All American 50 Finish

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday. Appropriate techniques should be applied to remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

Handle in accordance with good industrial hygiene and safety measures.

Wash hands and face after handling chemical products.

Wash hands before eating, drinking and smoking.

Wash hands at the end of the workday.

### **SECTION 9: Physical and chemical properties**

#### **Information on basic physical and chemical properties**

<b>Appearance</b>	pale yellow liquid
<b>Odor</b>	mild petroleum odor
<b>Odor threshold</b>	NA
<b>PH:</b>	NA
<b>Melting point/freezing point :</b>	NA
<b>Initial boiling point/range:</b>	161-198C (Stoddard Solvent)
<b>Flash point (closed cup):</b>	101F TCC
<b>Evaporation rate:</b>	0.18 (BuAc =1) (Stoddard Solvent)
<b>Flammability (solid, gas):</b>	NA
<b>Upper flammability/explosive limit:</b>	5.6% (Stoddard Solvent)
<b>Lower flammability/explosive limit:</b>	0.8% (Stoddard Solvent Solvent)
<b>Vapor pressure:</b>	27 KPa @ 20C (Stoddard Solvent)
<b>Vapor density:</b>	4.9 (Air = 1) (Stoddard Solvent)
<b>Density:</b>	0.89
<b>Relative density:</b>	NA

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 14/23

All American 50 Finish

<b>Solubilities :</b>	not soluble in water
<b>Partition coefficient (n-octanol/water):</b>	NA
<b>Auto/Self-ignition temperature:</b>	260C (Stoddard Solvent)
<b>Decomposition temperature:</b>	NA
<b>Dynamic viscosity:</b>	NA
<b>Kinematic viscosity:</b>	NA
<b>Explosive properties:</b>	NA
<b>Oxidizing properties:</b>	NA

### Other information

**VOC g/l:** 446 g/l

### SECTION 10: Stability and reactivity

**Reactivity:** Stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability:** Stable under normal storage and handling conditions.

**Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.

No dangerous reaction known under conditions of normal use.

**Conditions to avoid:** Incompatible materials.

Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

**Incompatible materials:** Strong oxidizing agents.

Strong oxidizing agents and strong acids.

**Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Carbon oxides (CO<sub>x</sub>).

### SECTION 11: Toxicological information

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 15/23

All American 50 Finish

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Route	Result
Distillates (petroleum), hydrotreated light	oral	LD50 >5000: Rat mg/kg
	dermal	LD50 >2000: Rabbit mg/kg
	inhalation	LC50 >5.28: Rat mg/L (4h Vapor)
Stoddard Solvent with < 0.1% Benzene content	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 5.5 mg/L (4 h)
	Dermal	LD50 Rabbit: >3000 mg/kg
Solvent naphtha (petroleum), heavy arom.	oral	LD50 Rat: >5000 mg/kg

### Skin corrosion/irritation

**Assessment:** Causes skin irritation.

**Product data:** No data available.

### Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes skin irritation.

### Serious eye damage/irritation

**Assessment:** Causes serious eye irritation.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 16/23

---

**All American 50 Finish**

**Product data:** No data available.

**Substance data:** No data available.

### Respiratory or skin sensitization

**Assessment:** May cause an allergic skin reaction.

**Product data:** No data available.

**Substance data:** No data available.

### Carcinogenicity

**Assessment:** May cause cancer.

**Product data:** No data available.

**Substance data:** No data available.

**International Agency for Research on Cancer (IARC):** None of the ingredients are listed.

**National Toxicology Program (NTP):** None of the ingredients are listed.

**OSHA Carcinogens:** Not applicable

### Germ cell mutagenicity

**Assessment:** May cause genetic defects.

**Product data:** No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Suspected of damaging fertility or the unborn child.

**Product data:** No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure) Assessment:

May cause drowsiness or dizziness.



## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 17/23

**All American 50 Finish**

---

### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (repeated exposure) Assessment:

Causes damage to organs through prolonged or repeated exposure.

**Product data:** No data available.

### Substance data:

#### Name

#### Result

Stoddard Solvent with < 0.1%	Causes damage to the Central Nervous System through prolonged or repeated exposure via inhalation.
Benzene content	

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

#### Name

#### Result

Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Stoddard Solvent with < 0.1% Benzene content	May be fatal if swallowed and enters airways.
Solvent naphtha (petroleum), heavy arom.	May be fatal if swallowed and enters airways.

**Information on likely routes of exposure:** No data available.

**Symptoms related to the physical, chemical and toxicological characteristics:** No data available.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 18/23

All American 50 Finish

**Other information:** No data available.

### SECTION 12: Ecological information

#### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Distillates (petroleum), hydrotreated light Magna: 170 - 226 mg/L (24 H)	LC50 Pimephales promelas: 41 - 45 mg/L (96 H) LC50 Oncorhynchus mykiss: 2.34 - 9.22 mg/L (96 H) EC50 Daphnia EC50 Selenastrum capricornutum (Algae): 19 - 56 mg/L (72 H)
Stoddard Solvent with < 0.1%	LC50 Oncorhynchus mykiss: 0.14 mg/L (96 hours)

Benzene content

#### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Result
Stoddard Solvent with < 0.1%	NOEC Oncorhynchus mykiss: 0.02 mg/L (30 d)

Benzene content

#### Persistence and degradability

**Product data:** No data available.

#### Substance data:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 19/23

All American 50 Finish

---

Name	Result
Stoddard Solvent with < 0.1%	Readily biodegradable.

Benzene content

### Bioaccumulative potential

**Product data:** No data available.

### Substance data:

Name	Result
Stoddard Solvent with < 0.1%	BCF: 39.66 L/Kg ww; Not considered to be bioaccumulative.

Benzene content

### Mobility in soil

**Product data:** No data available.

### Substance data:

Name	Result
Stoddard Solvent with < 0.1%	Koc at 20°C: 1451

Benzene content

### Results of PBT and vPvB assessment

#### Product data:

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

#### Substance data:

#### PBT assessment:

Stoddard Solvent with < 0.1%	The substance is not PBT.
------------------------------	---------------------------

Benzene content

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 20/23

All American 50 Finish

### vPvB assessment:

Stoddard Solvent with < 0.1%

The substance is not vPvB.

Benzene content

**Other adverse effects:** No data available.

### SECTION 13: Disposal considerations

#### **Disposal methods:**

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

#### **Contaminated packages:**

Not determined or not applicable.

### SECTION 14: Transport information

#### **United States Transportation of dangerous goods (49 CFR DOT)**

<b>UN number:</b>	1463
<b>UN proper shipping name:</b>	UN 1463, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
<b>UN transport hazard class(es)</b>	None
<b>Packing group</b>	III
<b>Environmental hazards:</b>	None
<b>Special precautions for user</b>	None
<b>Additional Information:</b>	May be classed as a Combustible Liquid for U.S. Ground.

#### **International Maritime Dangerous Goods (IMDG)**

<b>UN number:</b>	1463
<b>UN proper shipping name</b>	UN 1463, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
<b>UN transport hazard class(es)</b>	None

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 21/23

All American 50 Finish

Packing group	III
Environmental hazards	None
Special precautions for user	None
EMS number	1: F-E, 2: S-E

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1463
UN proper shipping name	UN 1463, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
UN transport hazard class(es)	None
Packing group	III
Environmental hazards	None
Special precautions for user	None
Passenger and cargo	355
Cargo aircraft only	366

### SECTION 15: Regulatory information

#### United States regulations

Inventory listing (TSCA):	All ingredients are listed or exempt.
Significant New Use Rule (TSCA Section 5):	None of the ingredients are listed.
Export notification under TSCA Section 12(b):	None of the ingredients are listed.
SARA Section 302 extremely hazardous substances:	None of the ingredients are listed.

#### SARA Section 313 toxic chemicals:

8001-26-1	Linseed Oil	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Not Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.10.2020

Page 22/23

---

### All American 50 Finish

8052-41-3 Stoddard Solvent with < 0.1% Benzene content Not Listed

64742-94-5 Solvent naphtha (petroleum), heavy arom. Not Listed

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

#### Massachusetts Right to Know:

8001-26-1 Linseed Oil Listed

64742-47-8 Distillates (petroleum), hydrotreated light Listed

8052-41-3 Stoddard Solvent with < 0.1% Benzene content Listed

64742-94-5 Solvent naphtha (petroleum), heavy arom. Listed

#### New Jersey Right to Know:

8001-26-1 Linseed Oil Not Listed

64742-47-8 Distillates (petroleum), hydrotreated light Listed

8052-41-3 Stoddard Solvent with < 0.1% Benzene content Listed

64742-94-5 Solvent naphtha (petroleum), heavy arom. Listed

#### New York Right to Know:

8001-26-1 Linseed Oil Not Listed

64742-47-8 Distillates (petroleum), hydrotreated light Listed

8052-41-3 Stoddard Solvent with < 0.1% Benzene content Listed

64742-94-5 Solvent naphtha (petroleum), heavy arom. Listed

#### Pennsylvania Right to Know:

8001-26-1 Linseed Oil Listed

64742-47-8 Distillates (petroleum), hydrotreated light Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial preparation date:** 02.10.2020

Page 23/23

---

### All American 50 Finish

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-94-5	Solvent naphtha (petroleum), heavy arom.	Listed

**California Proposition 65:** None of the ingredients are listed.

### **SECTION 16: Other information**

**Abbreviations and Acronyms:** None

#### **Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-2-0

**HMIS:** 2-2-0

**Initial preparation date:** 02.10.2020

**Revision date:** 07.22.2020

**End of Safety Data Sheet**